

CLASSIC

THE ORIGINAL ZODIAC® BOAT

Building on 70 years of heritage, the Classic incorporates the historic qualities that Zodiac® boats are known for: safety, stability, and strength. The Classic features generous seating and because of Zodiac's inflatable hull design, maneuvering, stability, and time to plane are legendary.

In the boat or on the roof of your car, you can take the Classic anywhere. It can be set up or stored in just a few simple steps. The Classic's features and quality will appeal to fishermen and pleasure boaters alike. Easily collapsible and compact, this boat can be transported without a trailer. These unique features have kept the Zodiac® boat successful for decades, and thye versatility attracts many types of customers.

Classic Mark II



Classic Mark II

EQUIPMENT



- Tried + tested design
- 2 floor options
- Easy set up/breakdown
- Easy storage and maintenance
- Navigation lights
- Accessory mounting rails
- Many optional accessories
- Strongan™ buoyancy tubes




Classic Mark II



CLASSIC MARK 1
3,5 m / 11'6"



CLASSIC MARK 2 C
3,8 m / 12'6"



CLASSIC MARK 2
4,2 m / 13'9"

DECK

- Choice of floors:
 - Quick-fit aluminium floor with tie-down rail system (Classic HD)
 - Marine plywood floor and aluminium frame with tie-down rail system (Classic ST)
- Inflatable hull
- Aluminium motor mounting plate
- 2 bailers

BUOYANCY TUBE

- Strongan™ 1100 decitex fabric
- Easy Push valves
- Polyamid lacing cuff + safety grab lines
- Wide anti-chafing deflector strip
- 1 bow handle
- 4 carrying handles
- 2 stainless steel tow rings
- Cone reinforcers

STANDARD EQUIPMENT

- Removable bow bag
- Fittings for remote steering bar
- Fittings for launching wheels
- Mast and pennant
- 2 carrying bags
- 2 paddles
- Foot pump
- 1 pressure gauge
- Repair kits
- Owner's manual

OPTIONAL EQUIPMENT

- 1 adjustable bench
- Luxury 2-person locker seat (except Mark 1)
- Inflatable bench
- Cover
- Fishing rod holder
- Launch trolley
- Launching wheels
- Electric pump
- Mini-console on bench
- Bathing ladder

TECHNICAL SPECIFICATIONS



	ZOOM SP		CLASSIC MARK 1		CLASSIC MARK 2C		CLASSIC MARK 2		FUTURA MARK 2C		FUTURA MARK 2		FUTURA MARK 3	
	400 ALU	450 ALU	ALU	SOLID	ALU	SOLID	ALU	SOLID	ALU	FR	ALU	FR	ALU	FR
DIMENSIONS (metres - feet/inches)														
Overall length	4 - 13'1"	4,5 - 14'9"	3,5 - 11'6"	3,5 - 11'6"	3,8 - 12'6"		4,2 - 13'9"		3,7 - 12'2"		4,1 - 13'5"		4,5 - 14'9"	
Inside length	3,2 - 10'6"	3,48 - 11'5"	2,3 - 7'7"	2,3 - 7'7"	2,55 - 8'4"		2,95 - 9'8"		2,6 - 8'6"		3 - 9'10"		3,4 - 11'2"	
Overall width	1,92 - 6'4"	1,92 - 6'4"	1,61 - 5'3"	1,61 - 5'3"	1,83 - 6'0"		1,83 - 6'0"		1,99 - 6'6"		1,99 - 6'6"		2,05 - 6'9"	
Inside width	0,90 - 2'11"	0,90 - 2'11"	0,77 - 2'6"	0,77 - 2'6"	0,92 - 3'0"		0,92 - 3'0"		0,89 - 2'11"		0,89 - 2'11"		0,9 - 2'11"	
Buoyancy tube diameter	0,50 - 1'8"	0,50 - 1'8"	0,425 - 1'5"	0,425 - 1'5"	0,455 - 1'6"		0,455 - 1'6"		0,55 - 1'10"		0,55 - 1'10"		0,575 - 1'11"	
CAPACITY														
Passengers (ISO)	7*	8*	5	5	6	6	7	7	6	5	7	6	9	8
Maximum payload ¹ (kg - lbs)	900* - 1984*	1000* - 2205*	590 - 1301	590 - 1301	750 - 1653	750 - 1653	840 - 1852	840 - 1852	860 - 1896	800 - 1764	1100 - 2425	1000 - 2205	1280 - 2822	1200 - 2646
Total weight (kg - lbs)	85 - 187	96 - 212	64 - 141	61 - 134	77 - 170	74 - 163	87 - 192	83 - 183	97 - 214	72 - 159	102 - 225	75 - 165	116 - 256	81 - 179
Airtight compartments	5 + 1	5 + 1	3 + 1	3 + 1	3 + 1	3 + 1	3 + 1	3 + 1	3 + 2 + 1	3 + 2 + 1 + 1	4 + 2 + 1	4 + 2 + 1 + 1	5 + 2 + 1	5 + 2 + 1 + 1
DESIGN CATEGORY														
European directive N° 94/25/CE	C	C	C	C	C	C	C	C	C	C	C	C	C	C
OUTBOARD DATA														
Shaft: ● Short ■ Long	●	■	●	●	●	●	●	●	●	●	■	■	■	■
Minimum recommended power ² (Hp)	20*	30*	6	6	8	8	10	10	15	8	20	10	25	10
Minimum recommended power ² (kW)	15*	23*	5	5	6	6	8	8	12	6	15	8	19	8
Maximum recommended power ² (Hp)	20*	30*	20	20	25	25	30	30	30	15	40	20	50	30
Maximum recommended power ² (kW)	15*	23*	15	15	19	19	23	23	23	12	30	15	38	23
Maximum power allowed ³ (Hp)	25*	40*	25	25	35	35	40	40	40	25	50	30	60	40
Maximum power allowed ³ (kW)	19*	30*	19	19	26	26	30	30	30	19	37	22	45	30
Maximum weight of outboard ⁴ (kg - lbs)	72* - 159*	95* - 209*	75 - 159	72 - 159	85 - 187	85 - 187	95 - 209	95 - 209	95 - 209	72 - 159	115 - 254	75 - 165	120 - 265	95 - 209
Maximum speed ⁵ (km/h - mph)			45 - 28	45 - 28	50 - 31	50 - 31	54 - 34	54 - 34	56 - 35	45 - 28	60 - 37	47 - 29	60 - 37	52 - 32
DIMENSIONS OF THE FOLDED BOAT (metres - feet/inches)														
Length of 1 st bag	1,27 - 4'2"	1,27 - 4'2"	1,3 - 4'3"	1,3 - 4'3"	1,44 - 4'9"	1,44 - 4'9"	1,44 - 4'9"	1,44 - 4'9"	1,4 - 4'7"	1,4 - 4'7"	1,4 - 4'7"	1,4 - 4'7"	1,4 - 4'7"	1,4 - 4'7"
Width of 1 st bag	0,69 - 2'3"	0,69 - 2'3"	0,6 - 1'12"	0,6 - 1'12"	0,65 - 2'2"	0,65 - 2'2"	0,68 - 2'3"	0,68 - 2'3"	0,75 - 2'6"	0,75 - 2'6"	0,75 - 2'6"	0,75 - 2'6"	0,75 - 2'6"	0,75 - 2'6"
Height of 1 st bag	0,30 - 0'12"	0,32 - 1'1"	0,35 - 1'2"	0,35 - 1'2"	0,35 - 1'2"	0,35 - 1'2"	0,35 - 1'2"	0,35 - 1'2"	0,63 - 2'1"	0,63 - 2'1"	0,63 - 2'1"	0,63 - 2'1"	0,63 - 2'1"	0,63 - 2'1"
Length of 2 nd bag	1,17 - 3'10"	1,17 - 3'10"	0,89 - 2'11"	0,89 - 2'11"	1,05 - 3'5"	1,05 - 3'5"	1,05 - 3'5"	1,05 - 3'5"	1,05 - 3'5"	-	1,05 - 3'5"	-	1,05 - 3'5"	-
Width of 2 nd bag	0,64 - 2'1"	0,73 - 2'5"	0,6 - 1'12"	0,6 - 1'12"	0,61 - 2'0"	0,61 - 2'0"	0,65 - 2'2"	0,65 - 2'2"	0,61 - 2'0"	-	0,65 - 2'2"	-	0,74 - 2'5"	-
Height of 2 nd bag	0,10 - 0'4"	0,11 - 0'4"	0,14 - 0'6"	0,14 - 0'6"	0,14 - 0'6"	0,14 - 0'6"	0,14 - 0'6"	0,14 - 0'6"	0,14 - 0'6"	-	0,14 - 0'6"	-	0,18 - 0'7"	-

* Awaiting approval

ENGINES

Indicated measurements may vary by +/- 3%, or +/- 5% for weight and speed measurements.

(1) Maximum permitted load is calculated using ISO standards. Caution is advised when operating fully laden boats.

(2) Recommended power is based on optimal use of the boat's abilities under average load. Depending on use, choose either maximum (waterskiing) or minimum power (fishing, cruising).

(3) The manufacturer's plaque specifies maximum permitted power. The power of your boat must not exceed this under any circumstances.

(4) Maximum permitted weight: dry weight, according to motor manufacturers' catalogue specifications.

(5) Maximum speeds are intended as a guide only; they were measured in ideal conditions by professional pilots with one person aboard. They may vary according to make of motor, boat load, propeller type and water conditions.

(6) Models in this catalogue are sometimes shown with optional accessories. Please check standard equipment supplied with each model and see your distributor for any additional equipment. The availability of certain models, as well as certain equipment details may vary from country to country (e.g. USA, Canada).

The boats photographed in this catalogue may differ from the actual models. Zodiac® Nautic continually strives to improve the quality of its products and as such reserves the right to modify or delete any model presented in this catalogue without prior notice. Zodiac® Nautic recommends that a life jacket is worn at all times; it is your own responsibility to check the legal obligations on your navigation zone.

This document may refer to trademarks belonging to other Companies. Such references are for identification only, and are not intended to be an endorsement. Whilst constantly seeking to improve its products, Zodiac® Nautic reserves the right to modify or improve the design or definition of its products at any time, without any prior notification and no retroactive effect on the boats built previously. This document cannot be considered as a contractual document. Non contractual pictures. Attitudes and behaviours of the persons aboard the boats must not be considered as an example.