

Cadet compact

RIB in a bag

Ein Festrumpf-Schlauchboot in einer Tasche



NEW

Thanks to its exclusive folding down transom, the Cadet Compact, once deflated, takes up very little space and is easy to store.

Dank seines exklusiven herunter klappbaren Heckspiegels, benötigt das Cadet Compact einmal entleert sehr wenig Platz und ist einfach zu verstauen.



- Choice of fabric: Strongan™ or Hypalon™ - Neoprene™
- RIMTEC polyester hull: low maintenance
- Available in white on Hypalon™ - Néoprène™ fabric versions
- Bootshaut Auswahl : Strongan™ oder Hypalon™ - Neopren™
- RIMTEC Polyesterrumpf: geringer Wartungsaufwand
- Hypalon™ - Néoprène™ -Gewebe Versionen sind in weiss erhältlich



Cadet Compact 250

Cadet Compact



Cadet Compact
250
2,5 m / 8'2"



Cadet Compact
300
3 m / 9'1"



COMPACT

Thanks to its fold-down rear transom – exclusive to ZODIAC® – the boat takes up very little space once deflated and can be simply stored in the specially designed bag.

This bag, with integrated handles, enables you to carry your boat in the simplest way possible – on the roof of your car or in a large boot. Setting up the boat is extremely rapid: simply inflate it, fit the oars and launch it!

Very light thanks to its RIMTEC (*Reinforced Injection Moulding Technology*) manufacturing process, its hull makes it comfortable and stable as well as providing excellent handling on the water. The large hollow interior allows a perfectly ergonomic seating position whilst also improving safety.

COMPACT 250

Dimensions (m - fi)		Capacity
Length overall	2.50 - 8'2"	Passengers (ISO) 3
Inside length	1.62 - 5'4"	Max payload allowed (Cat C) (Hp - kW) 400 - 882
Width overall	1.56 - 5'1"	Max payload allowed (Cat B) (Hp - kW) -
Inside width	0.70 - 2'4"	Total weight (kg - lbs) 38 - 84
Tube diameter	0.42 - 1'5"	Airtight compartments 2

Hull storage (m - fi)		Outboard data
Hull length:	1.76 - 5'9"	Shaft Short
Hull width	0.90 - 2'11"	Min recommended power (Hp - kW) 4 - 3
Hull height	0.30 - 1'0"	Max recommended power (Hp - kW) 6 - 5
Hull angle (°) -		Max power allowed (Hp - kW) 8 - 6
		Max speed (Km/h - mph) 28 - 17

COMPACT 300

Dimensions (m - fi)		Capacity
Length overall	3.00 - 9'10"	Passengers (ISO) 4
Inside length	2.02 - 6'8"	Max payload allowed (Cat C) (Hp - kW) 450 - 992
Width overall	1.56 - 5'1"	Max payload allowed (Cat B) (Hp - kW) -
Inside width	0.70 - 2'4"	Total weight (kg - lbs) 48 - 106
Tube diameter	0.42 - 1'5"	Airtight compartments 2

Hull storage (m - fi)		Outboard data
Hull length:	2.16 - 7'1"	Shaft Short
Hull width	0.90 - 2'11"	Min recommended power (Hp - kW) 6 - 5
Hull height	0.30 - 1'0"	Max recommended power (Hp - kW) 8 - 6
Hull angle (°) -		Max power allowed (Hp - kW) 10 - 8
		Max speed (Km/h - mph) 34 - 21

NEO

Hull

- V-shaped Rimtec hull
- Moulded non-slip deck
- Marine-ply folding transom
- 1 Bow D-ring
- 3 lifting points
- Fuel tank securing system
- Aluminium engine mounting plate
- 1 bailer

Buoyancy tube

- Hypalon™-Neoprene™ fabric
- Easy Push valves
- Handrail with fabric handles
- 2 Swivel oarlocks
- Broad rubbing strip
- 1 Bow handle
- 2 oar rests
- 2 stainless steel tow rings
- 2 carrying handles
- Cone reinforcers

Colour

Grey

Standard Equipment

- Transportation cover
- Removable thwart (dual position)
- Reinforced aluminium oars
- Foot pump
- Repair kit
- Owner's manual

Hull

- V-shaped Rimtec hull
- Moulded non-slip deck
- Marine-ply folding transom
- 1 Bow D-ring
- 3 lifting points
- Fuel tank securing system
- Aluminium engine mounting plate
- 1 bailer

Buoyancy tube

- Strongan™ fabric
- Easy Push valves
- Handrail with fabric handles
- 2 Swivel oarlocks
- Broad rubbing strip
- 1 Bow handle
- 2 oar rests
- 2 stainless steel tow rings
- 2 carrying handles
- Cone reinforcers

Colour

Grey

Standard Equipment

- Transportation cover
- Removable thwart (dual position)
- Reinforced aluminium oars
- Foot pump
- Repair kit
- Owner's manual