

NEW RANGE



Unique pla



The design of the new Pro Open Range is firmly focused on adventure boating, while providing a perfect balance of performance and comfort.

With excellent sea keeping qualities thanks to Zodiac® 's deep V-shaped hull and optimized deck plan, the Pro Open provides exceptional ride quality and comfort.

The Pro Open is designed in such a way that it can be easily transported, even with the buoyancy tubes inflated.

The Pro Open allows you to share your passion for boating with friends and family in style and comfort.

Your move!

The Points of the PRO OPEN

Special Technical Features

- Deep V-shaped hull
- Removable buoyancy tubes that are Zodiac® patented

On-board Comfort

- Ease of movement
- Self-draining deck
- Tilt steering console with storage area
- 54 litre cooler on the Pro Open 650
- 75 litre fuel tank (Pro Open 550) or 120 litre fuel tank (Pro Open 650)
- Navigation lights
- Bathing ladder

New Features

- Grey and orange (NEO) and grey and black (PVC) colours for the removable buoyancy tubes
- Three-place aft bench seat is standard on the Pro Open 550







The Pro Open 550 has a brandnew aft bench seat that three passengers for improved comfort when boating, whatever the sea conditions.
The adjustable centre seat allows a ski mast to be installed or the engine to be folded down in flash.









PVC



NE₀



NE₀

77 - 48

24°

| | PRO OPEN 550 | PRO OPEN 650 | |
|---|---------------|--------------|-----------------|
| DIMENSIONS (in metres – feet/inches) | | | |
| Overall length | 5,5 - 18'1" | 6,5 - 21'4" | |
| Inside length | 3,35 - 10'12" | 4,95 - 16'3" | |
| Overall width | 2,5 - 8'2" | 2,5 - 8'2" | |
| Inside width | 1,35 - 4'5" | 1,35 - 4'5" | |
| CAPACITY | | | |
| Number of passengers (ISO Cat B/C) | 11 | 5 / 13 | |
| Total weight (kg - lbs) | 440 - 970 | 670 - 1477 | |
| DESIGN CATEGORY | | | |
| European Directive No. 94/25/CE | C | B/C | |
| OUTBOARD DATA | | | |
| Shaft: ● Short ■ Long ★ Extra long ★ Ultra long | | mono 🗙 | bi 🔣 |
| Maximum recommended power ² (in Hp - kW) | 90 - 67 | 150 - 112 | - |
| Maximum power allowed ³ (in Hp - kW) 120 - 90 17 | | 175 - 131 | 2 x 80 - 2 x 59 |

Indicated measurements may vary by +/- 3%, or +/- 5% for weight and speed measurements. (1) Maximum permitted load is calculated using ISO standards. Caution is advised when operating fully laden boats. (2) Recommended power is based on optimal use of the boat's abilities under average load. Depending on use, choose either maximum (watersking) or minimum power (fishing, cruising). (3) The manufacturer's plaque specifies maximum permitted power. The power of your boat must not exceed this under any circumstances. (4) Maximum permitted weight of weight, according to make of more post and board. They may vary according to make of more post post and water conditions. (6) Models in this catalogue are sometimes shown with optional accessories. Please check standard equipment supplied with each model and see your distributor for any additional equipment. The availability of certain models, as well as certain equipment details may vary from country to country (e.g. USA, Canada). The boats photographed in this catalogue without prior notice. Zodiac® recommends that all fig lacket is wom at all times; it is your own responsibility to check the legal obligations on your ravigation zone.

*5 year warranty on tube fabric and 2 year warranty on hull and tube assembling. Some warranty extensions are available depending on product and geographical areas. For more information please contact your local dealer or visit zodiacmarine.com

EQUIPMENT

Maximum speed5 (in km/h - knots)

HULL

Hull angle

- Deep V-shaped polyester hull
- Moulded non-slip deck
- · Self-draining cockpit
- 1 bow ring
- 1 bow mooring post
- 2 stern mooring cleats
- Central hold
- Bow locker divided into two compartments:

Anchor locker

- + removable storage bin
- · 2 stern lockers
- 2 bailers

BUOYANCY TUBE

- Removable buoyancy tube
- Strongan™ Duotex™

- 2 x 1100 decitex fabric on the Pro Open 550 PVC model
- Hypalon[™]-Neoprene[™] 1100 decitex fabric on the Pro Open 550 NEO and 1670 decitex fabric on the Pro Open 650 NEO
- Polyester bow roller
- "Easy Push" valves
- Lateral lifelines
- 4 external handles
- TOMOGRAM TRAITMENT
- Ultra-wide anti-chafing deflector strip
- Short cones

STANDARD EQUIPMENT

- Reclining steering console cylinder with:
- · Steering wheel
 - + steering unit
 - + cable (550)
- Hydraulic steering (650)
- Pilot's and co-pilot's bolster with:

- FootrestHandrail
- 4 fishing rod holders

72 - 45

- Storage box
- Windscreen
- Stainless steel handrail
- Console doors
- Navigation lights
- Fitted fuel tank with gauge (75 litres on the Pro Open 550/ 120 litres on the Pro Open 650)
 - + water/fuel separator
- Bathing ladder
- Bilge pump
- Battery cut-off switch
- 2 paddles
- Foot pump
- 1 repair kit
- Owner's manual

EQUIPMENT SPECIFIC TO 550

3 aft passenger seats with adjustable centre seat

EQUIPMENT SPECIFIC TO 650

- Upholstered cooler seat (54 litres capacity)
- Aft seating with removable backrest
- Bathing ladder

OPTIONAL EQUIPMENT

- Removable backrest for bolster
- Bimini top
- Sundeck
- Ski mast
- Mooring awning

For more information, visit

PRO OPEN

The PRO OPEN sports a new look with a brand-new design. But it keeps all the features that made it a success. Its deep V-shaped hull lets it cut through the waves easily and smoothly, giving you a boat with optimum performance. Numerous options are available to make it an ideal companion for nautical sports, fishing or leisure. The swinging console built into the deck gives access to the built-in tank and a storage area.

The back bench seats up to 3 people and the central seat system makes it possible to lift the engine easily and use the ski pylon. This model is available in PVC as well as Hypalon[™]- Neoprene[™].

PRO OPEN 550

| Dimensions (m - fi) | | Capacity | |
|-------------------------------------|----------------|--------------------------------------|----------------|
| Length overal | l 5.50 - 18'1" | Passengers (ISO) | 11 |
| Inside length | 3.35 - 11'0" | Max payload allowed (Cat C) (Hp - k | W) 1450 - 3197 |
| Width overall | 2.50 - 8'2" | Max payload allowed (Cat B) (Hp - k' | W) - |
| Inside width | 1.35 - 4'5" | Total weight (kg - lbs) | 440 - 970 |
| Tube diametre | e 0.57 - 1'10" | Airtight compartments | 5 |
| Hull storage (m - fi) Outboard data | | | |
| Hull length: | 4.50 - 14'9" | Shaft | Long |
| Hull width | 1.70 - 5'7" | Min recommended power (Hp - kW) | 60 - 45 |
| Hull height | 1.80 - 5'11" | Max recommended power (Hp - kW) | 90 - 67 |
| Hull angle (°) | 24.0 | Max power allowed (Hp - kW) | 120 - 90 |
| | | Max speed (Km/h - mph) | 72 - 45 |

PRO OPEN 650

| Dimensions (m - fi) | | Capacity | |
|---------------------|-------------------------------------|--------------------------------------|----------------|
| Length overa | II 6.50 - 21'4" | Passengers (ISO) | 5 (B) / 13 (C) |
| Inside length | 4.95 - 16'3" | Max payload allowed (Cat C) (Hp - k | W) 1600 - 3527 |
| Width overall | 2.50 - 8'2" | Max payload allowed (Cat B) (Hp - k) | N) 1075 - 2370 |
| Inside width | 1.35 - 4'5" | Total weight (kg - lbs) | 670 - 1477 |
| Tube diametr | e 0.57 - 1'10" | Airtight compartments | 5 |
| Hull storaç | Hull storage (m - fi) Outboard data | | |
| Hull length: | 5.28 - 17'4" | Shaft | Extralong |
| Hull width | 1.57 - 5'2" | Min recommended power (Hp - kW) | 115 - 86 |
| Hull height | 1.80 - 5'11" | Max recommended power (Hp - kW) | 150 - 112 |
| Hull angle (°) | 24 0 | Max power allowed (Hp - kW) | 175 - 131 |
| | 21.0 | max perior anomou (rip itti) | |

Hull

- Deep V-shaped polyester hull
- Moulded non-slip deck
- Self-draining cockpit
- 1 bow ring
- 1 bow mooring cleat
- 2 stern mooring cleats
- Central hold
- Bow locker with separate compartments: anchor locker + removable storage bin
- 2 aft lockers

Buoyancy tube

Removable buoyancy tube

- Hypalon[™]-Neoprene[™] fabric
- Polyester bow roller
- Semi-recessed valves
- Lifelines
- 4 external handles
- Ultra-wide anti-chafing strip
- Short cones

Fabric

Hypalon, PVC thermobonded

Colour

Grey

Standard Equipment

- Reclining steering console cylinder with:
 - Hydraulic steering
 - Windscreen
 - o Stainless steel handrail
 - Console doors
- Navigation lights
- Fitted fuel tank with gauge (120 litres) + fuel/water separator
- Bilge pump
- Battery cut-off
- 2 paddles
- Foot pump
- Pressure gauge plug
- Repair kit
- Owner's manual

Equipment specific:

- Pilot and co-pilot's bolster with:
 - Foot-rests
 - o Handrail
 - 4 fishing rod holders
 - Storage bin
- Dual position upholstered 54-litre cooler
- Aft seat with removable backrest
- Bathing ladder