



NEW RANGE

ZODIAC® PRO

Don't just choose a boat,
choose your boat



Pro Classic 550



Pro Classic 550



Pro Touring 550



Pro Racing 550

The ideal boat represents the personality of its owner, its characteristics should be tailored to match the owner's boating interests.

With the remodeled Zodiac® Pro Range, owners finally have the chance to fully customize their boat.

Available in three model ranges, **CLASSIC**, **RACING** and **TOURING**, the **Zodiac® PRO** range offers unlimited choice – your choice. You design your boat by selecting the colour of its hull and buoyancy tube, the shape of the console, the bolster model, and the range of equipment best suited to your boating lifestyle.

The new **Zodiac® PRO** models are changing the rules of the game - mass-produced boats are a thing of the past! You're the boss!

Find out more about the three new model ranges:

- The **PRO CLASSIC** model: This legendary range now has a new, more dynamic look. Customers have the choice of either Strongan™DuoTex™ PVC or Hypalon™-Neoprene™ tubes, available in a variety of colours. With an enormous range of accessories and sizes from 4.2 to 7.5 metres, the options are endless.
- The **PRO RACING** model: This “high performance” boat has a sleek look thanks to its red black, and grey Hypalon™-Neoprene™ buoyancy tube. The Pro Racing model is ideal for boaters looking to indulge in water sports, and is available in 5 metre and 5.50 metre models.
- The **PRO TOURING** model: A fresh and vibrant model created for adventure, this highly inviting boat is sure to create unforgettable outings with family and friends. The Pro Touring range features a Strongan™DuoTex™ PVC fabric tube available in one of two colour schemes: Black/light grey or Royal Blue/light grey.

CONSOLES



	White console seat	Grey T4 console	Grey Optima 1000 XL console	Optima 1000 XL console	Grey Optima 800 console	White Optima 800 console	White Optima 800 FTC console	Grey Optima 800 FTC console	White two-seater jockey console	White jockey console
White PRO 420 hull						◆			◆	◆
Grey PRO 420 hull					◆					
White PRO 500 hull						◆	◆		◆	◆
Grey PRO 500 hull					◆			◆		
White PRO 550 hull	◆			◆		◆			◆	
Grey PRO 550 hull			◆		◆					
Grey PRO 650 hull			◆							
Grey PRO 750 hull		◆	◆							

SEATS



	Grey stainless steel bolster	White Optima bolster	Grey Optima bolster	White Optima 525 locker seat	Grey Optima 525 locker seat
White PRO 420 hull				◆	
Grey PRO 420 hull					◆
White PRO 500 hull		◆		◆	
Grey PRO 500 hull			◆		◆
White PRO 550 hull		◆		◆	
Grey PRO 550 hull	◆		◆		◆
Grey PRO 650 hull	◆		◆		◆
Grey PRO 750 hull	◆		◆		◆

Pro Classic 500



Pro Touring 500



PRO CLASSIC	420	500	550	650	750
HULLS					
Strongan™ Duotex™ PVC FABRIC BUOYANCY TUBE					
Hypalon™ - Neoprene™ FABRIC BUOYANCY TUBE					
PRO RACING	420	500	550	650	750
HULLS					
Hypalon™ - Neoprene™ FABRIC BUOYANCY TUBE					
PRO TOURING	420	500	550	650	750
HULLS					
Strongan™ Duotex™ PVC FABRIC BUOYANCY TUBE					

TECHNICAL SPECIFICATIONS



	PRO 420	PRO 500	PRO 550	PRO 650	PRO 750
DIMENSIONS (in metres – feet/inches)					
Overall length	4,2 - 13'9"	4,7 - 15'5"	5,2 - 17'2"	6,3 - 20'8"	7,5 - 24'7"
Inside length	2,90 - 9'6"	3,38 - 11'1"	4,02 - 13'2"	4,165 - 13'8"	6,16 - 20'38"
Overall width	1,90 - 6'3"	2,05 - 6'9"	2,2 - 7'3"	2,5 - 8'2"	2,9 - 9'6"
Inside width	0,95 - 3'1"	1,05 - 3'5"	1,2 - 3'11"	1,35 - 4'5"	1,65 - 5'4"
CAPACITY					
Number of passengers (ISO Cat B/C)	7	9	12	5 / 15	7 / 16
DESIGN CATEGORY					
European Directive No. 94/25/CE	C	C	C	B / C	B / C
MOTORSATION					
Shaft: ● Short ■ Long ✕ Extra long * Ultra long	■	■	■	mono ✕	bi ■
Maximum recommended power ² (in Hp - kW)	40 - 30	50 - 37	70 - 53	115 - 87	250 - 184
Maximum power allowed ³ (in Hp - kW)	50 - 37	70 - 52	90 - 67	150 - 112	250 - 184
Maximum speed ⁵ (in km/h - knots)	59 - 32	66 - 36	68 - 37	85 - 46	85 - 46
Hull angle	19°	22°	24,5°	24°	22°



Indicated measurements may vary by +/- 3%, or +/- 5% for weight and speed measurements. (1) Maximum permitted load is calculated using ISO standards. Caution is advised when operating fully laden boats. (2) Recommended power is based on optimal use of the boat's abilities under average load. Depending on use, choose either maximum (waterskiing) or minimum power (fishing, cruising). (3) The manufacturer's plaque specifies maximum permitted power. The power of your boat must not exceed this under any circumstances. (4) Maximum permitted weight; dry weight, according to motor manufacturers' catalogue specifications. (5) Maximum speeds are intended as a guide only; they were measured in ideal conditions by professional pilots with one person aboard. They may vary according to make of motor, boat load, propeller type and water conditions. (6) Models in this catalogue are sometimes shown with optional accessories. Please check standard equipment supplied with each model and see your distributor for any additional equipment. The availability of certain models, as well as certain equipment details may vary from country to country (e.g. USA, Canada). The boats photographed in this catalogue may differ from the actual models. Zodiac® continually strives to improve the quality of its products and as such reserves the right to modify or delete any model presented in this catalogue without prior notice. Zodiac® recommends that a life jacket is worn at all times; it is your own responsibility to check the legal obligations on your navigation zone.

*5 year warranty on tube fabric and 2 year warranty on hull and tube assembling. Some warranty extensions are available depending on product and geographical areas. For more information please contact your local dealer or visit zodiacmarine.com.

For more information, visit
www.zodiacmarine.com

Zodiac® is a registered trade mark - Copyright© Zodiac® 2013

PRO TOURING

A fresh, dynamic and user-friendly PVC range for unforgettable outings with family or friends. Available in blue or black & white (2 models of 5m and 5.50m), its polyester hull is either grey or white.

Totally adaptable thanks to its flat surfaces, PRO TOURING has whole range of additional accessories in white or grey that you can pick from to fit out your boat according to your tastes and needs.

PRO TOURING was designed with optimum onboard security in mind, which makes it particularly suitable for those who want to take lots of passengers on board.

Besides its non-slip deck, the boat's plating is higher to allow the transporting of pointed objects (spearguns, fish hooks, etc.) without needing to protect the float.

Packages are also available including consoles and seats to match your usage requirements.

PRO TOURING 500

Dimensions (m - fi)		Capacity	
Length overall	4.70 - 15'5"	Passengers (ISO)	9
Inside length	3.38 - 11'1"	Max payload allowed (Cat C) (Hp - kW)	1060 - 2337
Width overall	2.05 - 6'9"	Max payload allowed (Cat B) (Hp - kW)	-
Inside width	1.05 - 3'5"	Total weight (kg - lbs)	230 - 507
Tube diameter	0.50 - 1'8"	Airtight compartments	5
Hull storage (m - fi)		Outboard data	
Hull length:	3.82 - 12'6"	Shaft	Long
Hull width	1.38 - 4'6"	Min recommended power (Hp - kW)	40 - 30
Hull height	0.97 - 3'2"	Max recommended power (Hp - kW)	50 - 37
Hull angle (°)	22.0	Max power allowed (Hp - kW)	70 - 52
		Max speed (Km/h - mph)	66 - 41

PRO TOURING 550

Dimensions (m - fi)		Capacity	
Length overall	5.20 - 17'1"	Passengers (ISO)	12
Inside length	4.02 - 13'2"	Max payload allowed (Cat C) (Hp - kW)	1150 - 2535
Width overall	2.20 - 7'3"	Max payload allowed (Cat B) (Hp - kW)	-
Inside width	1.20 - 3'11"	Total weight (kg - lbs)	315 - 694
Tube diameter	0.50 - 1'8"	Airtight compartments	5
Hull storage (m - fi)		Outboard data	
Hull length:	4.46 - 14'8"	Shaft	Long
Hull width	1.53 - 5'0"	Min recommended power (Hp - kW)	40 - 30
Hull height	0.81 - 2'8"	Max recommended power (Hp - kW)	70 - 53
Hull angle (°)	24.5	Max power allowed (Hp - kW)	90 - 68
		Max speed (Km/h - mph)	68 - 42

Hull

- Deep V-shaped polyester hull
- Moulded non-slip deck
- 1 bow ring
- 2 tow rings
- Lockable bow locker
- 2 high volume bailer

Buoyancy tube

- Removable buoyancy tube
- Strongan™ Duotex™ 2 x 1100 decitex fabric
- Hypalon™-Neoprene™ fabric (optional)
- Easy push valves
- Polyamide lacing cuff + safety grab lines
- Non-slip patch
- Wide anti-chafing deflector fender
- 4 external handles
- 1 internal handle
- Cone reinforcers

Fabric

PVC thermobonded

Colour

Grey, Blue

Standard Equipment

- Integrated fuel tank + water/fuel separator : 75 litres
- Removable bow storage box
- 2 paddles
- Foot pump
- 1 pressure gauge plug
- Repair kit
- Owner's manual